


4-8
YEARS

WHIRL^{G1}

CONSTRUCTION MANUAL



Length 110 - 133 cm / 43 - 52 inch
Max weight 37 kg / 181 lbs
Time to build 1,5 hours



World's first real constructible rides



WARNING - IMPORTANT NOTICE TO PARENTS

Before you start constructing and use our product, please carefully read the following safety warning and download our manual from our website. This safety warning and manual contains important information relating to your child's safety. It is your responsibility to review this information with your child and make sure they are fully aware of all the warnings before they start riding. Failure to follow instructions and safety precautions can result in serious injury or death.

You can find a digital copy of the manual at the following web address:

www.infento.com

PLEASE PRINT OUT THE MANUAL AND KEEP THE MANUAL AND THIS **SAFETY WARNING** IN A SAFE LOCATION FOR FUTURE REFERENCE.

SAFETY SECTION



WARNING! PARENTAL SUPERVISION AND APPROPRIATE USE

Like any moving product, rides made from Infento parts can be dangerous if due care and attention is not paid. To reduce the risk of serious injury: use only under close adult supervision. Parents must review the following warnings and instructions with each Infento ride that is being built. It is your responsibility to review this information and make sure that all riders understand all warnings, cautions, instructions and safety topics, and assure that young riders are able to safely and responsibly use this product. Infento recommends that you periodically review and reinforce the information in this manual with younger riders, and that you inspect and maintain your child's Infento rides to insure their safety.

WARNING! RIDING ON INFENTO RIDES CAN BE A DANGEROUS ACTIVITY

Riding on Infento rides can be a dangerous activity. Certain conditions may cause the equipment to fail without fault of the manufacturer. Rides made from Infento parts can and are intended to move, and it is therefore possible to lose control, fall off and/or get into dangerous situations that no amount of care, instruction or expertise can eliminate. If such things occur you can be seriously injured or die, even when using safety equipment and other precautions. Ride at your own risk and use common sense.

WARNING! NO LIABILITY FOR CONSTRUCTED RIDES THAT DIFFER FROM OUR MANUALS

The rides that you can find in our manuals have been tested by official independent testing agencies. We will not be responsible or liable, directly or indirectly, in any way for any loss or damage of any kind incurred as a result of your decision to build constructions or rides that differ from the official rides that we show in our manuals.

ASSEMBLY – SUBSECTION

WARNING! OUR KITS CONTAIN SMALL PARTS

This package contains small parts which, before assembly, present a choking hazard to children under the age of three. Care should be taken

during unpacking and assembly to insure that all small parts and plastic bags are accounted for and kept out of the reach of children.

WARNING! TO AVOID SERIOUS INJURY:

1. Toys are to be assembled by an adult using Infento manuals.
2. All fasteners (bolts and nuts) should be fully tightened.
3. It is the responsibility of the adult who assembles this bicycle to properly install all parts included in the factory sealed shipping carton and to make the adjustments to the functional parts such as handle bar and seat and chain when necessary.

USE – SUBSECTION

WARNING! TO AVOID SERIOUS INJURY:

1. Continuous adult supervision is required.
2. Only ride constructed rides that have been built according to the instructions given in the official Infento manual.
3. Never exceed the maximum weight. You can find the maximum weight for every specific ride in our manual.
4. Always check the manual to see the minimum and maximum age as well as the minimum and maximum length for every specific ride.
5. Always wear safety equipment such as a helmet, knee pads and elbow pads. We recommend riders always wear a properly fitted helmet that complies with local or national guidelines or laws. Keep chinstrap of helmet securely buckled.
6. Always wear closed toed shoes (lace-up shoes with rubber soles), never ride barefooted or in sandals, and keep shoe laces tied and out of the way of the wheels.
7. Avoid streets and surfaces with water, sand, gravel, dirt, leaves, and other debris. Wet weather impairs traction, braking and visibility.
8. Excessive exposure to sunlight, temperatures below 0 degrees Celsius, water, sand, gravel, dirt, leaves, and other debris can damage, shrink, expand or weaken parts. Keep your ride in a dry environment with proper heating.
9. Avoid sharp bumps, drainage grates and sudden surface changes. Your Infento ride may suddenly stop.
10. Ride on smooth, paved surfaces away from motor vehicles. Wet, slick or uneven and rough

surfaces may impair traction and contribute to possible accidents.

11. Never risk damaging surfaces, such as carpet or flooring, by use of an Infento ride indoors.
12. Never use near motor vehicles, streets, roadways, alleys, swimming pool areas, hills, steps, sloped driveways, inclines and public highways.
13. Watch out for pedestrians, skaters, skateboards, scooters, bikes, children or animals who may enter your path, and respect the rights and property of others.
14. Avoid excessive speed associated with downhill rides.
15. Do not use at night or in periods with reduced visibility.
16. Before every use, please make sure that the complete ride and all joints have been assembled tightly, as with use, joints may wear out.
17. Before using your Infento ride, please check that the screws are tightened securely.
18. It's your own responsibility if you modify the product other than manufacturer's instructions.
19. Maintain a hold on the handlebars at all times.
20. Brake will get hot from continuous use. Do not touch after braking.
21. Periodically check hardware and tighten if necessary. Replace worn or broken parts immediately.
22. Skill is required to avoid falls or collision causing injury to the user and third parties.
23. Check operation of breaks every time before bicycle is ridden.
24. Check local laws before you start with riding.
25. Never tow wagons, other vehicles, or children on skates or skateboards.
26. Make certain that anyone who uses an Infento ride has been fully instructed in its operation.
27. Instruct your child on how to use the breaks.
28. Do not perform stunts.
29. Never use headphones or a cell phone when riding.
30. Only one rider at a time on an Infento ride.
31. Do not allow children to stand on the product at any time.

FAILURE TO USE COMMON SENSE AND HEED THE ABOVE WARNINGS INCREASES RISK OF SERIOUS INJURY. USE WITH APPROPRIATE CAUTION AND SERIOUS ATTENTION TO SAFE OPERATION.

SAFETY SECTION



OUR KITS CONTAIN SMALL PARTS

This package contains small parts which, before assembly, present a choking hazard to children under the age of three. Care should be taken during unpacking and assembly to insure that all small parts and plastic bags are accounted for and kept out of the reach of children.

QUESTIONS? HELP NEEDED?

You can email us at:
support@infento.com
and our team will assist you as soon as possible.



MAINTENANCE | INSTRUCTION



Inspect the product frequently. Failure to inspect the product and to make repairs or adjustments, as necessary, can result in injury to the rider or to others.

1. Make sure all parts are correctly assembled and adjusted as written in this manual.
2. Oil or grease moving parts periodically. Every 6 month.
3. Check nuts and bolts often and tighten if necessary. Every time you use your ride.
4. Any parts how are missing, showing evidence or wear should be replaced immediately.
5. Follow closely the assembly instructions pertaining to the proper adjustments of parts
6. Periodically check the brake system for proper function. Every time you use your ride.
7. Periodically check the steering mechanism for proper function. Every time you use your ride.
8. Check the air pressure in the tires to be the amount specified in the manual. Every time you use your ride.
9. Periodically check the bicycle's tooth belt to be sure that it is not too lose which could allow the chain to slip off the sprockets.


RECOMMENDED TOOLS



4 x Allen key
3, 4, 5, 6 mm



1 x Tapeline



1 x T-handle
for Allen key



5 x Wrench
10, 13, 14, 15, 19 mm



1

ride WHIRL

Bolt M8x20
(low head) 1x




Profile nut short 1x

T-Positioning block 2x

L-joint 1x


Profile 1x
9.45 inch | 240 mm

First, get all required materials stated here and then follow the instructions.



Tighten the bolts with full force. Ensure that you hold the long side of the Allen key in your hand as this enables you to exert greater force.

Double check here: Does your result look exactly like the image at the bottom of the page?




In frames like this you can find some background facts about technique.

TOP 3 REQUIREMENTS MAKING A GREAT INFENTO EXPERIENCE:



1

Tighten bolts with full force (15Nm) to prevent them from coming loose.



2

Constructing and playing always under supervision of an adult.



3

Check frequently if all parts are still firmly tightened and function properly.





2

ride WHIRL



Bolt M8x20
(low head) 1x

+



Profile nut short 1x

+






T-Positioning block 2x

+




L-joint 1x



Double check here:
Does your result looks exactly like
the image at the bottom of the
page?

Tighten the bolts with
full force. Ensure that
you hold the long side
of the Allen key in your
hand as this enables
you to exert greater
force.



Most nuts that you use
for Infento are self-locking.
This means that they cannot
vibrate loose. On the inside of
the bolt you will see a plastic
washer that ensures it cannot
turn freely, even if there is no
tension on the bolt.



3

ride WHIRL



1x

Bolt M8x20 nylock

+



4x



T-Positioning block

+



1x

Multi angle joint



The positioning blocks are some of the smallest Infento parts but they are also some of the most important. They ensure that everything connects to each other properly. This prevents parts from twisting and coming loose when under pressure. Therefore, always use at least two positioning blocks per block.





4

ride WHIRL


- 
 Bolt M8x25 (low head) 2x
- +
- 
 Positioning block 4x
- +
- 
 Locknut M8 2x
- +
- 
 Multi angle joint 2x
- +
- 
 Protect cap 1x

Use the Allen key handle so you can tighten the bolt well.



If your protect cap has a hole, use a M8x12 countersunk bolt to fasten it.

The positioning blocks are some of the smallest Infento parts but they are also some of the most important. They ensure that everything connects to each other properly. This prevents parts from twisting and coming loose when under pressure. Therefore, always use at least two positioning blocks per block.










5

ride WHIRL

- 
Bolt M8x20
- +
- 
Profile nut short
- +
- 
T-Positioning block
- +
- 
Multi angle joint
- 1x
- 1x
- 2x
- 1x







6

ride WHIRL

- Bolt M8x20 4x
- T-Positioning block 8x
- Multi angle joint 4x
- Profile 4.72 inch | 120 mm 2x










7

ride WHIRL

- 
Bolt M8x35
- +
- 
Locknut M8
- +
- 
Knurled disc 2 stripes



There are two types of knurled discs. Please see education section.








There are two different knurled discs. One for each corner ending in a 5 (5-15-25-etc. degrees), which has one stripe round the outside, and one for each corner that ends in a 0 (0-10-20-etc degrees), which has two stripes round the outside.



8

ride WHIRL










9

ride WHIRL

- Bolt M8x40 nylock (low head) 1x + T-Positioning block 4x + Positioning block 4x + L-joint 1x + Swivel plate 2x






10



ride WHIRL

If your Kit contains a white fastener bag with 12 Nock Washers, please follow the steps on this page. If not, please skip to the next page of the manual.



2x
Nock washer M8-16



This is the 4" Swivel Wheelhouse. Before being able to use this part, you need two Nock Washers M8-16. Press these washers into the slots.











11

ride WHIRL

-  1x
- +
-  1x
- +
-  1x
- +
-  1x
- +
-  1x



If your **Swivel Fork 4" Wheel** contains a metal bearing on top (instead of a red plastic ring), you can skip this step!





12

ride **WHIRL**

Bolt M8x60 1x

+

Positioning block 2x

+

Washer M8-16 3x

+



Connector Swivel fork 4 inch wheel 1x

+

Locknut M8 1x

+

Washer M8-24 1x




If your **Swivel Fork 4"** **Wheel** contains a metal bearing on top, add a Washer M8-16 between the bearing and the Washer M8-24.



Washer M8-16 1x

TIP!
It is best to tighten the bolt in such a way that you can still move the block and easily determine the right position with a tape measure. After that, you can then tighten the block further and you verify whether the size is correct.










13

ride WHIRL



- Bolt M8x40 nylock (low head) 1x
- T-Positioning block 4x
- Positioning block 4x
- L-joint 1x
- Swivel plate 2x











14

ride WHIRL

-  1x
-  1x
-  1x
-  1x
-  1x



If your **Swivel Fork 4" Wheel** contains a metal bearing on top (instead of a red plastic ring), you can skip this step!









15

ride WHIRL

- Bolt M8x60 1x + Positioning block 2x + Washer M8-16 3x + Connector Swivel fork 4 inch wheel 1x + Locknut M8 1x + Washer M8-24 1x



If your **Swivel Fork 4"** **Wheel** contains a metal bearing on top, add a Washer M8-16 between the bearing and the Washer M8-24.





16

ride WHIRL



2x

+



Locknut M8





2x

+



Knurled disc 2 stripes

2x









17

ride **WHIRL**

-  2x
-  2x
-  4x
-  2x







18

ride WHIRL

- Bolt M8x20 2x
- Bolt M8x20 (low head) 2x
- T-Positioning block 8x
- Multi angle joint 2x
- L-joint 2x
- Profile 3.15 inch | 80 mm 2x







19

ride WHIRL

- Bolt M8x25 (low head) 2x
- Positioning block 4x
- Locknut M8 2x
- Multi angle joint 2x





20

ride WHIRL



Bolt M8x35 2x

+





Locknut M8 2x

+






Knurled disc 2 stripes 2x

A





B








21

-  +
 -  +
 -  +
 - 
- Square nut M6 4x Bolt M6x50 4x Seatboard Tail 2x Seatboard Base 1x

If you have this type of seat in your Kit, please skip to the next page. If not, follow the instructions below to construct your seatboard.





22

ride WHIRL



Seatboard

1x






Bolt M8x16
(low head)

2x



Profile nut short

2x







23

ride WHIRL

-  Bolt M8x25 2x
-  Locknut M8 2x
-  Multi angle joint 2x
-  Seatboard 1x





24

ride WHIRL




2x

+



2x

+




2x

Bolt M8x35


Locknut M8

Knurled disc 2 stripes



A



B







C





25

ride WHIRL





26

ride WHIRL



+





+



T-Positioning block 2x

Bolt M8x20 (low head) 1x


L-joint 1x









27

ride WHIRL



Depending on your Kit, the T-joint might look like this. The new T-joint doubles as a profile connector (part A)





28

ride WHIRL



Bolt M8x20
(low head) 1x

+




T-Positioning block 2x

+




L-joint 1x

+







Profile 1x
11.02 inch | 280 mm





29




ride WHIRL





30

ride WHIRL







31

ride WHIRL

If your Kit contains a white fastener bag with 12 Nock Washers, please follow the steps on this page. If not, please skip to the next page of the manual.




2x
Nock washer M8-16









32

ride WHIRL

- 
Bolt M8x20 1x
- + 
Profile nut short 1x
- + 
T-Positioning block 2x
- + 
U-Block 1x



If your U-block or Kit doesn't have the M8-16 Nock Washers, you can use the regular M8-16 washers as shown here.








33

ride WHIRL

-  1x
- +
-  1x
- +
-  4x
- +
-  1x
- +
-  1x
- +
-  1x



Use the Allen key handle so you can tighten the bolt well.










34

ride WHIRL


If your U-block or Kit doesn't have the M8-16 Nock Washers, you can use the regular M8-16 washers as shown here.









35

ride WHIRL

-  1x
-  1x
-  2x
-  1x








36

ride WHIRL

-  1x
- +
-  1x
- +
-  4x
- +
-  1x
- +
-  1x
- +
-  1x



Use the Allen key handle so you can tighten the bolt well.









37

ride WHIRL

- Bolt M8x60 1x + Locknut M8 1x + Washer M8-16 2x





38

ride WHIRL



Bolt M8x20
(low head) 1x

+



Profile nut short 1x

+




T-Positioning block 2x

+





L-joint 1x


A



B




0.98" | 25 mm








39

ride WHIRL

- 
1x
Bolt M8x20 nylock
- +
- 
4x
T-Positioning block
- +
- 
1x
Bearing protection cap
- +
- 
1x
Bearing block 40x40_Hexa 19



Use the Allen key handle so you can tighten the bolt well.








40

ride WHIRL

- 
Bolt M6x16
- +
- 
Conical spring washer M6-10
- +
- 
Brake caliper holder
- +
- 
Brake caliper





41

ride **WHIRL**



Bolt M8x20
(low head) 1x

+



Bolt M5x6 2x

+






Locknut M8 1x

+




Caliper shield 1x










42

ride **WHIRL**






-  Bolt M8x20 1x
-  Spacer 0.04inch | 1mm 1x
-  Washer M8-24 1x
-  Axle 6.54 inch | 166 mm 1x
-  Pedal left 1x
-  Crank large left 1x





43

ride WHIRL





44





ride WHIRL



Spacer 1x
0.2 inch | 5 mm



Brake disc 1x





45

ride WHIRL



Bolt M6x12





5x




13 inch
Driven wheel

1x




After tightening the second nut, check if the wheel is still rotating with the desired resistance.










46

ride WHIRL

-  5x Bolt M8x20
-  1x Spacer 0.08inch | 2 mm
-  1x Washer M8-24
-  1x Crank large right
-  1x Pedal right





47

ride WHIRL



2x

+



2x

+






2x

Bolt M8x35

Locknut M8




Knurled disc 1 stripe





48

ride WHIRL





49

ride WHIRL



1x

Bolt M8x35

+



1x




Locknut M8

+



1x

Knurled disc 2 stripes







50

ride **WHIRL**

-  +
-  1x
- +  1x
- +  1x
- +  1x
- +  1x





51

ride WHIRL



1x

Bolt M8x35

+



1x




Locknut M8

+



1x


Knurled disc 2 stripes





52

ride WHIRL







Brake lever left 1x

+




Protect cap 1x














53

ride WHIRL



Handgrip 2x












55


ride WHIRL













56

ride WHIRL



Brake cable 1x
27.56 in | 700 mm












58

ride WHIRL



WHIRL^{G1}



THANK YOU FOR READING ME!